

LT-591

Single Needle, Lockstitch, Post-Bed Type Basting Machine

EXCLUSIVE BASTING MACHINE TO INCREASE SEWING EFFICIENCY AND PRODUCTIVITY



LT-591

Feature

Application

This machine is best suited for basting process of not only men's suits, ladies' suits, coats, etc., but also for basting of front interlining, basting of front facing, basting of front, basting of pad, etc.







Bobbin thread changing time is reduced to 1/5

In order to overcome the weakness of rapid consumption of the bobbin thread, the amount of wound bobbin thread is increased to over 5 times that of previous modeles. Thus the bobbin therad changing time is more shortened than the previous models and naturally the production efficiency is greatly upped.

Post-bed type with wide applicability

As either a flat-bed type or a high wooden buck type auxiliary table can be used, the usage is very wide.

Accurate basting by automatic stop

When the treadle is stepped on, the machine stars and when the foot is released, the machine always stops at a required position. Therefore, the machine can be stopped at each stitch and thus, this is an ideal machine for basting of complicated process which demands accurate basting.

Quiet and positive running

Another feature is the correct timing belt which is used to drive the main shaft and the hook driving shaft. This ensures quiet and positive running of the machine.

SPECIFICATIONS

Sewing speed	Max 600 sti/min
Stitch length	Free (without feed mechanism)
Needle bar stroke	52.8mm (2-5/64")
Presser lifting amount	Max. 35mm (1-3/8")(by hand)
Needle	TV x 7 #14 (Standard)
Sewing hook	Vertical rotary hook
Feed system	Without feed mechanism (manual)
Lubrication	Hand oiling system
Bed size	440 x 178mm
Machine head weight	53kg

^{*&}quot;sti/min"stands for "Stitches per Minute"







Registered Organization : JUNI CORPORATION Head Office The Scope of the Registration : The activities of research development, design, sales, distribution, and maintenance services of industrial sewing machines, household semignachines and industrial robots, etc., including sales and maintenance services of rata entry several.

• To order, please contact your nearest JUKI distributor.



2-11-1, TSURUMAKI, TAMA-SHI, TOKYO 206-8551, JAPAN PHONE: (81) 42-357-2370 FAX: (81) 42-357-2274

FAX: (81) 42-357-2274 http://www.juki.com

 $[\]begin{tabular}{ll} \bigstar Specifications and appearance are subject to change without prior notice for improvement. \end{tabular}$

^{*} Read the instruction manual before putting the machine into service to ensure safety.

 $[\]ensuremath{\bigstar}$ This catalogue prints with environment-friendly soyink on recycle paper.