

**PFAFF**<sup>®</sup> Industrial

## PFAFF 5626

2-needle longarm post-bed unison feed  
chainstitch sewing machine



## Area of application:

Two-needle decorative seams on large, bulky and voluminous parts (leather, technical applications, dashboards)

## Features:

- High seam quality and stitch reliability due to optimized sewing kinematics, even in case of thick threads
- High traction due to unison feed (bottom feed and alternating top and needle feed)
- Increased performance by means of bobbin less chainstitch technology, high sewing speed and variable stitch length
- The 5696 work with parallel located loopers which move in sewing direction (Inline)
- High top feed stroke: max. 4 mm
- Fabric clearance under the foot: max. 11 mm
- High-adjustable single-column stand - thus ensures an easy handling when sewing large, bulky and voluminous parts
- Option: Mirrored hooks for parallel top-stitching and fancy seams (no sawtooth optics)
- Option: Handwheel can be switched electronically via control panel
- Further fittings on request

## Technical data:

- Max. sewing speed: 1,200 s.p.m.
- Stitch length (max.): 6.0 mm
- Needle gauges: 6.0 to 8.0 mm
- Needle system: 62-57
- Thread size (max.): 11/3 syn
- Needle size: 100 - 140 Nm

## **PFAFF Industriesysteme und Maschinen GmbH**

Hans-Geiger-Str. 12 – IG Nord  
D-67661 Kaiserslautern

Telefon: +49-6301/3205-0  
Telefax: +49-6301/3205-3171  
E-mail: [info@pfaff-industrial.com](mailto:info@pfaff-industrial.com)

